

# RENEGADE

THOMAS  Pro-Series

Built for Contractors – Built to Last



T-100SP



T-100ST

#### HIGH-QUALITY COMPONENTS

By using high-quality fittings, gauges and other components, the Renegade® Pro-Series provides the ultimate integrity of a long, service-free life.

#### PERMANENTLY LUBRICATED DESIGN

Means Renegade® Pro-Series starts quickly, even in the coldest of weather.



#### ELECTRICALLY FRIENDLY

Low current draw won't blow standard 15 AMP house circuits and extension cords can be used whenever and wherever you need one.



**PATENTED LIFE-GUARD™ DIRT DEFLECTOR** keeps job site dust and grit out of the compressor.



	T-100SP	T-100ST
Air Displacement	6.0 CFM	6.0 CFM
Air Delivery	3.1 CFM @ 100 PSI Max pressure to 135 PSI	3.1 CFM @ 100 PSI Max pressure to 135 PSI
Pressure Switch	Starts compressor @ 110 PSI Stops compressor @135 PSI	Starts compressor @ 110 PSI Stops compressor @ 135 PSI
Motor	1 HP electric motor Capacitor start	1 HP electric motor Capacitor start
Tanks Capacity	3 gallons	4 gallons
Shipping Weight	57 lbs.	66 lbs.
Net Weight	52 lbs.	61 lbs.
Dimensions: Unit L x W x H (in.): Ctn.	15 x 15 x 24 18.4 x 18.4 x 25.4	18.87 x 14.63 x 16.38 22.0 x 16.5 x 17.3
Low Amp Draw	13.0	13.0
Recovery Time	18 seconds	22 seconds
Regulator & Gauge	Supplied	Supplied
RPM	1725	1725
Decibel Rating	75 dB	75 dB
Finish Guns	3-4	3-4
Framing Guns	1-2	1-2
Roofing Guns	1-2	1-2

Quality Compressors for the Professional Contractor.



# RENEGADE

THOMAS  Pro-Series

Built for Contractors – Built to Last



T-200ST



T-200

**HIGH-QUALITY COMPONENTS**

By using high-quality fittings, gauges and other components, the Renegade® Pro-Series provides the ultimate integrity of a long, service-free life.

**PERMANENTLY LUBRICATED DESIGN**

Means Renegade® Pro-Series starts quickly, even in the coldest of weather.



**ELECTRICALLY FRIENDLY**

Low current draw won't blow standard 15 AMP house circuits and extension cords can be used whenever and wherever you need one.



**PATENTED LIFE-GUARD™ DIRT DEFLECTOR** keeps job site dust and grit out of the compressor.



	T-200ST	T-200
Air Displacement	8.0 CFM	8.0 CFM
Air Delivery	4.6 CFM @ 100 PSI Max pressure to 135 PSI	4.6 CFM @ 100 PSI Max pressure to 135 PSI
Pressure Switch	Starts compressor @ 110 PSI Stops compressor @ 135 PSI	Starts compressor @ 110 PSI Stops compressor @ 135 PSI
Motor	2 HP electric motor Capacitor start/run	2 HP electric motor Capacitor start/run
Tanks Capacity	4 gallons	7 gallons
Shipping Weight	72 lbs.	101 lbs.
Net Weight	66 lbs.	90 lbs.
Dimensions: Unit L x W x H (in.): Ctn.	19 x 14.6 x 16.3 22 x 16.5 x 17.3	42.1 x 18 x 22.2 45 x 19.5 x 28.5
Low Amp Draw	13.0	13.0
Recovery Time	12 seconds	20 seconds
Regulator & Gauge	Supplied	Supplied
RPM	1725	1725
Decibel Rating	75 dB	75 dB
Finish Guns	5-6	5-6
Framing Guns	3-4	3-4
Roofing Guns	3-4	3-4

Quality Compressors for the Professional Contractor.

